

VALUE SERIES

Speed & Efficiency

Standardized panel sizes have been strategically developed to optimize material utilization, simplify fabrication, and accelerate installation.



OVERVIEW



CLADLOK™ VS (Value Series) provides a fast, economical solution, delivering smooth, level flat panels with clean lines that install vertically or horizontally to suit a variety of design visions. The modular cassette-style system features interlocking edges formed from a single piece of metal — no additional components beyond the fasteners — supporting fast, efficient installation without compromising architectural quality. Custom panel sizes can be accommodated when required, with pricing adjusted to reflect material yield and manufacturing efficiency.

FEATURES

- Economical
- Non-Combustible
- 100% Recyclable
- Pressure Equalized Rainscreen
- 20 Year Finish Warranty on Painted Options
- Integrates with a variety of backup wall assemblies
- Streamlined Installation
- Little to No Maintenance
- Reduced Lead Times
- Made in the USA

SYSTEM CONFIGURATION

PANEL LAYOUT OPTIONS AND KEY SPECIFICATIONS



KEY SPECIFICATIONS

Configuration: Fixed module sizes; grid, stack & running bond pattern
System Depth: 1-3/4"
Reveal: 1/2" Reveal

STANDARD PANEL SIZES

18W x 30H	24W x 48H	42W x 30H	72W x 24H
24W x 24H	30W x 30H	48W x 24H	96W x 24H
24W x 30H	30W x 60H	54W x 30H	

All dimensions in inches (W x H). Custom sizes available upon request. Pricing adjusts according to material utilization.

MATERIALS

Material & Finish Options

ALUMINUM (3003)	
0.080" Prefinished or Post Painted	0.063" Prefinished Only

FINISH NOTES

- 2- 3 Coat 70% PVDF / Standard AAMA 2605
- 2 & 3 Coat Solid and Mica Finishes
- 20 Year Finish Warranty on Painted Options
- No exotic or printed finishes with Value Series
- Custom color matching available upon request

PERFORMANCE

Testing

Tested to applicable AAMA and ASTM standards. Detailed performance data available upon request.

- | | |
|--|---|
| <ul style="list-style-type: none"> • AAMA 508-7 Pressure Equalized Rainscreen Test • AAMA 501.1-05 Dynamic Water Infiltration Test • ASTM E283-04 Static Air Infiltration | <ul style="list-style-type: none"> • ASTM E330-02 Structural Design loads (40psf) • ASTM E331-02 Static Water Infiltration • ASTM E1233-06 Standard for Structural Performance |
|--|---|

DELIVERY

Transitions, Logistics & Deliverables

The VALUE Series includes field-applied trims and closures; flat sheet material is available upon request. Two-piece CLADLOK® extrusions are also an option.

LOGISTICS

Delivery: Expedited delivery schedule
Minimum Order: 500 SQFT per color/size